AirMotion Smart MPT™ Fans

Smart use of advanced technologies now comes affordable

The most affordable and effective large diameter HVLS fan on market. Intelligently designed with our Massive Performance Technology (MPT™), Smart MPT Fans move and mix two to three times more air than other HVLS fans. We have fitted the Smart MPT line with our Multimode Smart Control that provides you with manual to fully automatic fan control with on-board smart electronics and temperature sensors.



Specifications for Smart MPT-24, Smart MPT-20, and Smart MPT-16

- > FAN SPEED
- > BLADE PITCH
- > CFM
- > APPROXIMATE WEIGHT
- > FAN MOTOR
- > GEAR REDUCER
- > MAX OPERATING WATTS
- > FULL LOAD AMPS

220-240/1 208-240/3 380/3 460-480/3

> VFD

- > NUMBER OF FAN BLADES
- > FAN BLADE MATERIAL
- > BLADE MOUNTING SHAFTS
- > FAN CONTROLLER
- > FAN CONTROLLER DIMENSIONS
- > FAN CONTROLLER WIRE

> OPERATING MODES

MANUAL DESTRAT AUTOMODE EXTERNAL

- > MOTOR/POWER UNIT CHASSIS
- > MOTOR/POWER UNIT DIMENSIONS
- > MOUNTING OPTIONS

SINGLE POINT 4 POINT

> SAFETY

UP TO 50 RPM FOR 24 FT FAN | UP TO 60 RPM FOR 20 FT FAN | UP TO 80 RPM FOR 16 FT FAN OPTIMIZED FOR POWER AND PERFORMANCE

UP TO 710,000 FOR 24 FT FAN | UP TO 514,000 FOR 20 FT FAN | UP TO 350,000 FOR 16 FT FAN 280 LBS FOR 24 FT FAN | 260 LBS FOR 20 FT FAN | 240 LBS FOR 16 FT FAN

COMPACT 3 HP TEFC HIGH EFFICIENCY - ADAPTABLE TO ANY POWER SOURCE ALUMINUM BODY AND PRECISELY MACHINED HIGH STRENGTH STEEL GEARING WITH HEAVY DUTY BEARINGS AND SEALS. LUBED FOR LIFE

2,250

8 5.4 - 4.7 3

HIGH QUALITY US MADE

6

EXTRUDED ALUMINUM

HIGH STRENGTH MACHINED STEEL

REMOTE MOUNTED 12V LOW VOLTAGE MICROPROCESSOR CONTROL

APPROXIMATELY 5" X 5" X 3" SHEET METAL ENCLOSURE 4 CONDUCTOR THERMOSTAT OR TELECOM WIRE

USER SELECTS SPEED AND DIRECTION FOR DOWNWARD OR UPWARD AIRFLOW

FAN TURNS ON AND OFF BASED ON TEMPERATURE DIFFERENCES AT USER SET SPEED AND DIRECTION

FAN SELECTS SPEED BASED ON TEMPERATURE DIFFERENCES

FAN TURNS ON AND OFF USING EXTERNAL INPUTS

PAINTED SHEET METAL ENCLOSURE AND COMPONENT FOR MOUNTING

APPROXIMATELY 18" X 15.5" X 8.5"

FACTORY FABRICATED UNIVERSAL BEAM CLAMP

UNISTRUT, THREADED ROD OR OTHER

MULTIPLE SAFETY CABLES, WIRES, AND ELECTRICAL DEVICES



AirMotion Sciences, Inc. Boston, MA

Call us at 508-653-3500 or e-mail to info@airmotionsciences.com www.airmotionsciences.com